

Updates on the Optical Levitation Experiment

Yuta Michimura,

Department of Physics, University of Tokyo


michimura@phys.s.u-tokyo.ac.jp



Hiroki Chiyoda, Takuya Kawasaki, Jerome Degallaix


Optical Levitation of Mirror

- Support a mirror with **radiation pressure alone**
- **Free** from suspension thermal noise
- **Large coupling** compared with optical tweezers




Sandwich Configuration


- Mirror levitation have never been realized
- Simpler configuration than previous proposals
 - YM, Y. Kuwahara+, [Optics Express 25, 13799 \(2017\)](#)
- Proved that stable levitation is possible and **SQL can be reached** with **0.2 mg mirror**



S. Singh+: [PRL 105, 213602 \(2010\)](#)




G. Guccione+: [PRL 111, 183001 \(2013\)](#)



Levitated mirror

Stability of Levitation


- Rotational motion is stable with **gravity**
- Vertical motion is stable with **optical spring**
- Horizontal motion is stable with **cavity axis change**
- *Curved mirror is necessary!*



Reaching SQL

- **Constraint on design:** intra-cavity power to support the mass
- **0.2 mg** fused silica mirror, Finesse of 100, 13 W + 4 W input

Low finesse necessary for cavity pole to be higher than SQL reaching frequency





Experiment to Verify the Stability

- **Verified the stability** with a torsion pendulum and a dummy mirror

T. Kawasaki, ..., YM,
[PRA 102, 053520 \(2020\)](#)

Measured optical geometrical spring agreed with expectation



Fabrication of Levitation Mirrors

- mg and mm-scale curved mirror necessary
e.g. For levitation demonstration
 φ 3 mm, 0.1 mm thick (~ 1.6 mg for fused silica)
RoC = **~ 30 mm convex**
R > 99.95 %
- Two approaches
 1. Coat **thin fused silica mirror** to bend the mirror
 2. **Photonic crystal mirror** to create effective curvature




New Approach for Fused Silica

2014 Approach

(1) Make 3 mm dia. lens




(2) Coat



CRACKED!

2020-2021 Approach


(1) Make 1 inch dia.
0.1 mm thick disk



(2) Coat (bend due to stress)



(3) Cut into 3 mm dia.



Thin Fused Silica Mirror Updates






- Sep 2020: **R>~90% ϕ 1 inch** mirrors arrived
 - Two samples, measured to be No AR coating yet
 - (1) R=92(1)%, RoC=500⁺²⁰⁰⁰₋₂₀₀ mm
 - (2) R=88(1)%, RoC=400⁺⁸⁰⁰₋₂₀₀ mm
 - Somehow concave, although convex is expected probably we measured flipped mirror
- Jan 2021: **T=10ppm ϕ 1 inch** mirrors arrived
 - Expected to have RoC of -450 mm ~6 um thick coating
- June 2021: Cut **T=10ppm ϕ 3 mm** mirrors arrived
 - 27 remained
 - cleaning of the protective layer wasn't great & many broke during the process Coating thickness x2
-> RoC x~1/2
Substrate thickness x1/4
-> RoC x~1/16
-> Diameter x2
- Now trying to make **25 um thick** wafers
 - Final cut process could be skipped

Photonic Crystal Mirror

- **Effective curvature** possible by modulating the filling factor

M. S. Seghilani+,
[Optics Express 22, 5962 \(2014\)](#)

- So far trying Si photonic crystal mirror without modulation
 So far achieved 95(5) % reflectivity



Summary

- **Milligram scale mirror** can be levitated with realistic parameters
YM, Y. Kuwahara+, [Optics Express 25, 13799 \(2017\)](#)
- Succeeded in experimentally verifying the **stability** of the levitation
T. Kawasaki, ..., YM, [PRA 102, 053520 \(2020\)](#)
- Trying two approaches for the **fabrication** of a milligram mirror with high reflectivity and curvature
 - Coated **thin fused silica mirror**
R~90% achieved with RoC~500 m
Next: thinner wafer with thicker coating
 - **Photonic crystal mirror**
R~95% achieved without modulation
Next: higher reflectivity and modulation