

GWADW2021 Gravitational Wave Advanced Detector Workshop



Report of Abstracts

Abstract ID : 39

Design of Coupled Wave Front Sensor for Torsion-Bar Antenna

Content

TOBA (Torsion-Bar Antenna) is a ground-based gravitational wave detector using a torsion pendulum. The resonant frequency of torsional motion is ~ 1 mHz, therefore TOBA has good design sensitivity of $10^{-19} / \sqrt{\text{Hz}}$ at 0.1 Hz in low frequencies (0.1 Hz – 10 Hz). TOBA can detect intermediate mass black hole binary mergers and so on. A prototype detector Phase-III TOBA with a 35 cm-scale pendulum is under development to demonstrate noise reduction. The target sensitivity is set to $10^{-15} / \sqrt{\text{Hz}}$ at 0.1 Hz. To achieve our target sensitivity, we need to measure the pendulum rotation precisely. We propose a coupled wave front sensor as an angular sensor for Phase-III TOBA. In our method, an auxiliary cavity is used to enhance the first-order TEM modes in the main cavity. We will show the principle and experimental design of a coupled wave front sensor in this workshop.

Primary author: OSHIMA, Yuka (University of Tokyo)

Co-authors: TAKANO, Satoru (University of Tokyo); OOI, Ching Pin (University of Tokyo); MICHIMURA, Yuta (University of Tokyo); ANDO, Masaki (University of Tokyo)

Presenter: OSHIMA, Yuka (University of Tokyo)

Track Classification: Low frequency workshop

Contribution Type: poster

Submitted by **OSHIMA, Yuka** on **Saturday 01 May 2021**