

**GWADW2022 - Approaching
the low-frequency design
sensitivity of ground-based
detectors**

Report of Abstracts

Abstract ID : 13

Angular Signal Amplification with a Coupled Cavity for Torsion-Bar Antenna

Content

Torsion-Bar Antenna (TOBA) is a ground-based gravitational wave detector using a torsion pendulum. The resonant frequency of torsional motion is ~ 1 mHz, therefore TOBA has good design sensitivity of $10^{-19} / \sqrt{\text{Hz}}$ at 0.1 Hz in low frequencies (0.1 Hz – 10 Hz). TOBA can detect intermediate mass black hole binary mergers, Newtonian noise, and so on. A prototype detector Phase-III TOBA with a 35 cm-scale pendulum is under development to demonstrate noise reduction. The target sensitivity is set to $10^{-15} / \sqrt{\text{Hz}}$ at 0.1 Hz. To achieve our target sensitivity, we need to measure the pendulum rotation precisely. We propose a coupled wavefront sensor (Coupled WFS) as an angular sensor for Phase-III TOBA. In our method, an auxiliary cavity is used to compensate Gouy phase of a main cavity and enhance the first-order TEM modes in the main cavity. The experimental demonstration was successfully performed in 2021. In this workshop, we will show the principle and demonstration results of a Coupled WFS.

Primary author: OSHIMA, Yuka (University of Tokyo)

Co-authors: Mr TAKANO, Satoru (University of Tokyo); Mr OOI, Ching Pin (University of Tokyo); Dr MICHIMURA, Yuta (California Institute of Technology); Prof. ANDO, Masaki (University of Tokyo)

Track Classification: Instrument status: lessons and challenges for low frequencies; Technical noises for low frequencies

Contribution Type: Poster presentation

Submitted by **OSHIMA, Yuka** on **Monday 18 April 2022**